

## TT MEDIATEX<sup>®</sup> ART-TEX SE

Spezifikation (Specification)	Einheit (unit)	Norm (standard)	Wert (value)
Substrat : (substrate)		(DIN 60001)	100% BW 100% cotton
Flächengewicht: (weight)	[g/m <sup>2</sup> ]	(DIN EN ISO 2286-2)	380 ±20
Materialdicke (thickness)	[mm]	(DIN EN ISO 2286-3)	0,60± 0,05
Reißkraft K/S (tensile strength warp/weft)	[daN/5cm]	(DIN 53857 T1)	> 70/55
Weiterreißkraft K/S (tear resistance warp/weft)	[N]	(DIN 53857 T2)	> 15/12
Weißgrad (whiteness)		( nach Berger)	85- 100
Lichtechtheit (light fastness)	[Note] [grade]	(DIN EN ISO 105-B02)	≥ 6
Schwerentflammbarkeit: (flame retardant)		(DIN 4102 B1)	ja yes
Tintentyp (type of ink)			wässrige Pigment-Tinten waterbased pigment ink
Anwendung (use)			innen indoor
Breite : (width)	[cm] [inch]	(DIN EN ISO 2286-1)	91,4; 106,7; 127; 137; 152,4 36; 42; 50; 54; 60
Druckseite: (printsides)			außen outside
Rollenlänge (length of the roll)		( - )	15 ± 0,5

<p>The article TT Mediatex<sup>®</sup> Art-Tex SE is onesided triple coated with a special polymercoating which allows a high whiteness. Additionally you get a highly brilliant print at a maximum of dyestuff yield.</p> <p>TT Mediatex<sup>®</sup> Art-Tex SE is the only genuine canvas for art reproductions, which is flame resistant as 100% natural fiber. TT Mediatex<sup>®</sup> Art-Tex SE delivers the best print results with 3K inks from Epson.</p>	<p>TT Mediatex<sup>®</sup> Art-Tex SE has been tested with the following printers:</p> <p style="text-align: center;">HP 5500 • Epson • Canon • etc.</p> <p style="text-align: center;">Please see for yourself at a test.</p>
--	--

All details are nominal values and are subject to change within usual tolerances (±5%).  
All information conforms to our latest knowledge and is not legally binding.  
Subject to change.

date: 07/2007